

# Production Range for Special Shaped Hollow Sections

Type	Outside Diameter (mm) (AxBxC)	Wall Thickness (mm)											
		0,5	0,6	0,7	0,8	0,9	1,0	1,2	1,4	1,5	2,0	2,5	3,0
		Mass Per Unit Length (kg/m)											
Oval Profile	30X15	0,31	0,38	0,43	0,50	0,55	0,61	0,73	0,84	0,89	1,18	1,45	1,72
Oval Profile	40X16	-	0,48	0,55	0,64	0,72	0,80	0,95	1,11	1,19	1,55	1,88	2,21
Oval Profile	40X20	-	0,51	0,59	0,68	0,76	0,84	1,00	1,16	1,24	1,63	1,98	2,33
Oval Profile	50X25	-	-	-	0,82	0,91	1,01	1,22	1,41	1,51	1,99	2,47	2,94
Oval Profile	50X32	-	-	-	0,87	0,97	1,08	1,29	1,49	1,60	2,12	2,63	3,13
Elliptical Profile	40X20	-	0,47	0,55	0,62	0,70	0,78	0,92	1,07	1,14	1,51	1,86	2,21
D-Profile	40X30	-	-	-	0,80	0,90	0,99	1,19	1,38	1,47	1,95	2,41	2,87
28 L-Profile	12.5 x 25 x 28	-	-	-	-	-	-	1,24	1,41	1,53	2,03	2,46	3,01
28 T-Profile	12.5 x 25 x 28	-	-	-	-	-	-	1,45	1,71	1,80	2,39	2,99	3,56
28 Z-Profile	12.5 x 25 x 28	-	-	-	-	-	-	1,45	1,71	1,80	2,39	2,99	3,56
33 L-Profile	15 x 30 x 33	-	-	-	-	-	-	1,45	1,71	1,80	2,39	2,99	3,56
33 T-Profile	15 x 30 x 33	-	-	-	-	-	-	1,74	2,03	2,16	2,86	3,56	4,26
33 Z-Profile	15 x 30 x 33	-	-	-	-	-	-	1,74	2,03	2,16	2,86	3,56	4,26

## Length Range

	4,0 - 8,0 m
	4,0 - 8,5 m

