

## Certificate of Conformity of the Factory Production Control 2195-CPR-1629401

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

### Cold formed welded structural hollow sections of non-alloy steels made of the following steel grades

(tested for performance for the characteristics described in Annex 1 which is an inseparable part of this certificate)

produced by the manufacturer

#### TOSÇELİK PROFİL VE SAC END. A.Ş.

Organize Sanayi Böl. Necati Özsoy Cad. No:12, 31200 İskenderun / Hatay – Turkey

and produced in the manufacturing plant

#### TOSÇELİK PROFİL VE SAC END. A.Ş.

Organize Sanayi Böl. 5. Kısım 5007. Sok. No:22 Dilovası / Kocaeli – Turkey


This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

### EN 10219-1: 2006

under system 2+ are applied and that the factory production control is assessed to be in conformity with the applicable requirements. This certificate was first issued on 20.10.2016, renewed on 20.10.2024 and will remain valid as long as neither the harmonised standard, the construction product, the assessment and verification of constancy of performance methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit, the period validity date is renewed every year after the surveillance audits.

Validity Date : 20.10.2027

Period Validity Date : 20.10.2025



Rukiye BALKAN  
Deputy General Manager



FR. CPR. 24 R:04

## Certificate of Conformity of the Factory Production Control

2195-CPR-1629401

### Annex 1

#### Intended uses;

To be used in metal structures or in composite metal and concrete structures.

#### Controlled Performance Characteristics;

- Dimension and Shape Tolerances,
- Yield Strength,
- Elongation,
- Tensile Strength,
- Impact Resistance,
- Weldability.

Steel Grade	Section	Dimensions
S235JRH S275J0H S275J2H S275NH S275NLH S275MH S275MLH	Circular hollow sections	Ø from 17,20 mm up to 273,00 mm wall thickness: from 0,60 mm up to 10,00 mm
S355J0H S355J2H S355K2H S355NH S355NLH S355MH S355MLH	Square hollow sections	from 10 mm x 10 mm up to 200 mm x 200 mm, wall thickness: from 0,60 mm up to 10,00 mm
S420MH S420MLH S460NH S460NLH S460MH S460MLH	Rectangular hollow sections	from 10 mm x 15 mm up to 150 mm x 250 mm, wall thickness: from 0,60 mm up to 10,00 mm

  
Rukiye BALKAN  
Deputy General Manager

FR. CPR. 24 R:04